



SMS SMMS Spunbond-Meltblown-Spunbond Nonwoven

Layo offers all specifications of SMS SMMS Spunbond-Meltblown-Spunbond Nonwoven, SMS consists of continuous 100% polypropylene (PP) threads arranged at random and thermally welded by a calendering process, or Spunlaid thermobonded method, plus a meltblown layer and then another of spunbonded polypropylene. Any inquiries and problems please feel free to send emails to us and we will reply you soon.

Find a huge selection of **SMS SMMS Spunbond-Meltblown-Spunbond Nonwoven**, Bico(PE/PP) Spunbond Nonwoven from China at LAYO. Provide professional after-sales service and the right price, looking forward to cooperation.

China based supplier of **SMS SMMS Spunbond-Meltblown-Spunbond Nonwoven**. This is a high coverage nonwoven fabric. Its low weight, high longitudinal and transversal strength and soft feel make it suitable for use in the medical and hygiene industry. It can be given special treatments to give it certain properties (hydrophilic, anti-bacterial, oil-repellent, alcohol-repellent and blood-repellent).

Product Features

SMS SMMS Spunbond-Meltblown-Spunbond Nonwoven With suitable treatments during the SMS manufacturing process, different product types can be obtained for specific applications.
HYDROPHILIC: SMS is normally hydrophobic, but hydrophilic treatment will enable liquids to pass through.

ANTIBACTERIAL: Fibres with antibacterial treatment protect the material from bacteria and fungi.

ANTI-MITE: Fibres with an anti-mite treatment that protects the material from dust mites.

ANTI-STATIC: Treatment helps neutralize static electric charges in the fabric.

ALCOHOL AND BLOOD REPELLENT: Treatment against alcohol and blood helps repel these substances so the product can be used in the medical and health sector.

OIL-REPELLENT: The oil repellent treatment helps repel oil and can be used for applications where this is required.

HYDROSTATIC PRESSURE RESISTANCE.

If you have any interest on specific item, please reach us for a TDS

Product Specifications

China based supplier of Spunbond+Meltblown+Spunbond Nonwoven. Below the specification range:

Width: max.320cm

Basis weight: 15gsm~200gsm

Spin finish: standard hydrophobic or hydrophilic

Piagment available:yes

Product Production And Delivery Display Diagram

